

# HP Compaq Tablet PC tc4400



\$1825.00

<b>Main Specifications</b>	
Product Description	HP Compaq Tablet PC tc4400 - Core 2 Duo T7200 2 GHz - 12.1" TFT
Dimensions (WxDxH)	11.2 in x 9.3 in x 1.3 in
Weight	4.6 lbs
Localization	English / United States
Windows Vista Certification	Windows Vista Capable
System Type	Tablet PC - convertible
Built-in Devices	Speaker, wireless LAN antenna
Embedded Security	Trusted Platform Module (TPM 1.2) Security Chip , fingerprint reader
Processor	Intel Core 2 Duo T7200 / 2 GHz ( Dual-Core )
Cache Memory	4 MB - L2 cache
RAM	2 GB (installed) / 4 GB (max) - DDR II SDRAM - 667 MHz
Card Reader	Yes
Hard Drive	120 GB - Serial ATA-150 - 5400 rpm
Display	12.1" TFT active matrix 1024 x 768 ( XGA ) - up to 16.2 million colors
Graphics Controller	Intel GMA 950
Audio Output	Sound card
Telecom	Fax / modem - MDC - 56 Kbps
Networking	Network adapter - Ethernet, Fast Ethernet, Gigabit Ethernet, IEEE 802.11b, IEEE 802.11a, IEEE 802.11g, Bluetooth 2.0 EDR
Input Device	Keyboard, digitizer, touchpad, pointing stick, digital pen
Power	AC 120/230 V ( 50/60 Hz )
Battery	Lithium ion
Run Time (Up To)	5.5 hour(s)
Operating System	Microsoft Windows XP Tablet PC Edition
Manufacturer Warranty	3 years warranty
<b>General</b>	
Windows Vista Certification	Windows Vista Capable

System Type	Tablet PC - convertible
Built-in Devices	Speaker, wireless LAN antenna
Embedded Security	Trusted Platform Module (TPM 1.2) Security Chip , fingerprint reader
Width	11.2 in
Depth	9.3 in
Height	1.3 in
Weight	4.6 lbs
Localization	English / United States
<b>Processor</b>	
Processor	Intel Core 2 Duo T7200 / 2 GHz
Multi-Core Technology	Dual-Core
64-bit Computing	Yes
Data Bus Speed	667 MHz
Chipset Type	Mobile Intel 945GM Express
<b>Cache Memory</b>	
Type	L2 cache
Installed Size	4 MB
<b>RAM</b>	
Installed Size	2 GB / 4 GB (max)
Technology	DDR II SDRAM - 667 MHz
Form Factor	SO DIMM 200-pin
<b>Storage Controller</b>	
Type	Serial ATA
Serial ATA Interface	Serial ATA-150
<b>Storage</b>	
Hard Drive	120 GB - Serial ATA-150 - 5400 rpm
<b>Card Reader</b>	
Type	Card reader
Supported Flash Memory Cards	SD Memory Card, MultiMediaCard
<b>Display</b>	
Display Type	12.1" TFT active matrix
Max Resolution	1024 x 768 ( XGA )
Widescreen Display	No
Color Support	Up to 16.2 million colors
Features	Ambient light sensor
<b>Video</b>	
Graphics Processor / Vendor	Intel GMA 950

Video Memory	Dynamic Video Memory Technology 3.0
Max Allocated RAM Size	224 MB
<b>Audio</b>	
Audio Output	Sound card
Audio Codec	AD1981HD
Compliant Standards	Sound Blaster Pro, High Definition Audio
Audio Input	Microphone
<b>Input Device(s)</b>	
Type	Keyboard, digitizer, touchpad, pointing stick, digital pen
<b>Telecom</b>	
Modem	Fax / modem - MDC
Max Transfer Rate	56 Kbps
Protocols & Specifications	ITU V.21, Bell 212A, ITU V.22, ITU V.22bis, ITU V.29, ITU V.32, ITU V.32bis, ITU V.34, ITU V.17, ITU V.23, ITU V.27ter, Bell 103J, ITU V.8, ITU V.92, ITU T.30, ITU T.4, ITU V.250, ITU V.251, ITU V.80
Fax Compatibility	G3
<b>Networking</b>	
Networking	Network adapter
Wireless LAN Supported	Yes
Data Link Protocol	Ethernet, Fast Ethernet, Gigabit Ethernet, IEEE 802.11b, IEEE 802.11a, IEEE 802.11g, Bluetooth 2.0 EDR
Bluetooth Class	Class 2
Compliant Standards	IEEE 802.3, IEEE 802.3u, IEEE 802.3i, IEEE 802.3z, IEEE 802.3ab, IEEE 802.1p, IEEE 802.11b, IEEE 802.11a, IEEE 802.3x, IEEE 802.11g, Wi-Fi CERTIFIED
<b>Expansion / Connectivity</b>	
Expansion Slots Total (Free)	2 memory - SO DIMM 200-pin 1 ( 1 ) x CardBus - type I/II
Interfaces	2 x Hi-Speed USB - 4 pin USB Type A 1 x PoweredUSB 2.0 - 4 pin USB Type A 1 x display / video - VGA - 15 pin HD D-Sub (HD-15) 1 x display / video - S-video output 1 x microphone - input - mini-phone stereo 3.5 mm 1 x audio - line-out/headphones - mini-phone stereo 3.5 mm 1 x modem - phone line - RJ-11 1 x network - Ethernet 10Base-T/100Base-TX/1000Base-T - RJ-45 1 x infrared - IrDA 1 x docking / port replicator 1 x battery
<b>Miscellaneous</b>	
Features	Security lock slot (cable lock sold separately), system password, power-on password, DriveLock, memory change alert, HP ProtectTools Embedded Security
Compliant Standards	CE, CSA, UL, BSMI, GOST, EPA Energy Star, GS, SABS, SASO, CCC, MIC
<b>Power</b>	

Power Device	External
Voltage Required	AC 120/230 V ( 50/60 Hz )
<b>Battery</b>	
Technology	6-cell lithium ion
Installed Qty	1
Capacity	5100 mAh
Run Time (Up To)	5.5 hour(s)
<b>Operating System / Software</b>	
OS Provided	Microsoft Windows XP Tablet PC Edition
<b>Manufacturer Warranty</b>	
Service & Support	3 years warranty
Service & Support Details	Limited warranty - parts and labor - 3 years Limited warranty - battery - 1 year
<b>Environmental Parameters</b>	
Min Operating Temperature	32 °F
Max Operating Temperature	95 °F
Humidity Range Operating	10 - 90%
Shock Tolerance	125 g @ 2ms half-sine pulse (operating) / 200 g @ 2ms half-sine pulse (non-operating)
Vibration Tolerance	0.75 g @ RMS (random) (operating) / 1.5 g @ RMS (random) (non-operating)